



Guardex

WALK THROUGH METAL DETECTOR GRD-UB 500

12 zones standard

PARAMETERS :

Power Supply : AC85V-264V
 Working Temperature : -20°C--+50°C
 Working Frequency : 4KHZ—8KHZ
 Standard External size : 2200mm(H)X800mm(W)X500mm(D)
 Standard Internal size : 2010mm(H)X700mm(W)X500mm(D)
 Package size for door panels : 2260*645*235mm *1ctn
 Package size for control unit : 420*740*235 mm*1ctn
 Gross weight : 72KG

CHARACTERISTIC & FUNCTION :

- * Six mutual over-lapping detecting zones, Simultaneous alarm from multi- zones;
- * Sensitivity adjustable; Each zone has 100 sensitivity level
- * Sound & LED alarm; Both Side LED indicator , easily show where the metal is.
- * Automatically count passengers and alarm times
- * Alarm strength indicator on control panel
- * Password protection, only the authorized person can operate.
- * Easy assembly; designed with only 2 pieces cables and 8 screws, simply-to-follow instruction.
- * Harmless to human body; is harmless with heart pacemaker, pregnant women, magnetic floppy, recording tapes, etc.
- * Using high density fireproof material
- * Program Self-diagnostic when power on,no need initial or periodic calibration
- * Modularization design,easy for maintenance and replacement.
- * Sensitivity Test piece: One Metal Coin, omnidirectional detection
- * 4-8 hours backup battery (Option)

Application

Exhibition center, Electronic Factory, Bank, Prison, Government office,Hotel etc



bilmak
security systems

T : 0 212. 225 80 50 pbx
 M : bilmak@bilmak.com.tr
 www.bilmak.com.tr



RoHS
COMPLIANT

ISO
9001

