
## AUT ► CLEAR CheckGate® 8000C and 9000C

## Compact Column Weapons Portal





CheckGate®: Easy to operate, view and maintain, with 64-character backlit LCD, large alarm LEDs and adjustable tones.

### **Features and Benefits**

### **→** Clever discrimination

The 9000C automatically double screens each person, saving valuable time and manpower with its unique multifield transmitter and receiver pairs on **both** portal sides.

#### → Reliable and robust

No melamine, brittle plastic, bulbs, or entry sensors to replace or repair. Environmentally robust and friendly.

### **⇒** Lightest weight, portable column design

Rounded columns allow for greater overall visibility. Very lightweight, portable and robust in architectural granite/marble composite. Lightest and toughest portal anywhere.

### **→** Lowest false alarm rates

Fastest checkpoint processing, even at the highest threat levels.

### → Advanced signal processing

Uniquely filters out RFI/EMI "noise" from surrounding electronic monitors, devices and systems.

### **⇒** Easy set-up and care

Setting detection levels, volume, tone and features is simple, yet secure.

### **⇒** Fast, automatic calibration

Nulls out metal around portal sides.

### → Model 8000C version

The 8000C version detects all metal threats, with advanced signal processing and uniform detection top to bottom.

### **→** Quality compliant

CE compliant, medically safe, lowest emissions/power, FAA approved. American design and manufacture. Highest ISO 9001 certified.

# *Ultimate Portability, & Performance*

Events • Schools • Secret Service • Military
Police • Architectural • Hotels • Banks • Rentals • Media

Leading contraband threat detection & field support, since 1937



Scintrex® • CheckGate® • Dynavision® • Control Screening® • Federal Labs® U.S. Canada Europe Dubai Latin America Beijing Hong Kong Singapore

## CheckGate® 8000C/9000C technical specifications

AUT (\*) CLEAR CheckGate® 9000C provides extremely low false alarm rates and offers the highest throughput traffic flow. Unique patented multiple paired antenna coils marginalize false alarms on personal items, providing maximum detection and maximum reliability. The lowest false alarm and highest threat object detection rates are assured in the busiest and toughest security environments. CheckGate® portals are also available in mulitizone configurations. Ask for details.

CheckGate® 8000C has been engineered to be cost effective and as attractive, durable and reliable as the Model 9000C, with the same strong noise immunity and ease of use.

### Standard Features of 9000C

- DSP circuitry eliminates spikes, noise, and two-way radio interference.
- No Sensors are required—detection circuitry is continuously active.
- LCD display indicates settings, diagnostic functions and operational menus. Large, bright LED indicators for power and alarm status.
- Diagnostics are built in and circuits are constantly monitored for faults.
- 100 standard programs, ferrous and nonferrous metal detection.
- Sensitivity range settings are selectable from 0 to 99 for accurate target detection.
- · Cable-free installation with four selectable ring-tones. Remote alarm relay and data output connector.
- · One year warranty on all parts and labor—extended warranty available. Lifetime no chip or crack warranty on portal side materials.

### **Unique Performance Qualities of 9000C**

- · Unique dual coil system and powerful software provide multi-field detection throughout, yielding by far the lowest false alarm rate, for the widest range of targets.
- · Left-to-right, right-to-left, top-to-bottom, and bottom-to-top positions detect any target, eliminating "strong" and "weak" sides. No comparable model comes close.
- · Custom programs are configured via built-in menu prompts, allowing further enhancement for unique targets or environments.
- Magnetic field lower by 50%, minimizing moving metal interference at the front and exit.
- The portal self adjusts to withstand environmental interference from large static metal objects and heavy local RFI. A dual channel bargraph meter makes it easy to optimize performance in busy locations.
- The portal can be optimized to the local floor construction. Detection at ankle level or below is easily adjustable (using less than two parameters).

### **Performance Standards**

### **Electronics**

### **Portal**

field coils.

### **Power**

### **Environmental Conditions**

### **Dimensions & Weight**

Overall Loop Assembly Passageway Clearance Net Weight Optional Mounting Plates

**Options** 

- · Remote Command Center
- 24" and Custom Widths
- Remote Annunciator Panel
- · Formica Color, Construction
- · Floor Anchor Kit
- · Wheels or No Tools Hardware
- Compact, Column Model 9000C

Meets and exceeds NILECJ standard 0601.00 level 1-5, ICAO, FCC and F.A.A. Airport Security Regulations.

Microprocessor computer controlled circuitry with 12 digit keypad entry control, LCD display, LED bargraph meter & audio/visual alarm.

Architectural, seamless thermoplastic houses multi-

Standard composite: Blue-grey granite. Select 9000C (Compact, Column) or 8000C (Compact, Column) Industrial grade power supply 90-265 VAC (<1Amp), 50/60 Hz +/- 3 Hz Temperature: -10°C to 55°C

Humidity: 0-98%, non-condensing

47"W x 90"H x 9"D (119cm x 229cm x 22cm) 30"W x 81"H (76cm x 206cm) 50 lbs. (23 kg) 10 lbs. each (optional)

Battery Backup

 Matching Key Side Table 14.7"W x 23.3"D x 38"H (37cm W x 59cm D x 96cm H)

· Person Counter, Sensor

Weatherization

### Built-in Power Conditioner

CE Marking

Leading contraband threat detectio field support, since 1937



www.autoclearus.com

www.scintrextrace.com www.fed-labs.com

Scintrex® • CheckGate® • Dynavision® • Control Screening® • Federal Labs® Canada Europe Dubai Latin America Beijing Hong Kong Singapore





**Distributor:** 

ISO 9001-2000 Certified

U.S. Pat. 5,397,986

www.autoclearus.com

Fairfield, NJ 07004-2206 USA

Technology Labs &

**Headquarters Plant** 

Tel: 1 (973) 276-6161

Fax: 1 (973) 276-6162 info@autoclearus.com

eu@autoclearus.com

Tel: + 33 2 38 61 97 00

Fax: + 33 2 38 61 97 01

seu@autoclearus.com

neu@autoclearus.com

Canada & Scintrex

Tel: 1 (613) 224-1061 Fax: 1 (613) 224-2603

Asia Southeast & North

sasia@autoclearus.com

nasia@autoclearus.com china@autoclearus.com

latina@autoclearus.com

ME@autoclearus.com

Tel: + 971 6 557 4505 Fax: + 971 6 557 4507

**Latin America** 

Middle East

Western U.S. sw@autoclearus.com

Dubai, UAE

info@scintrextrace.com

300 Parkdale Ave., Ottawa Ontario, Canada K1Y 1G2

2 Gardner Road

**Central EU** 

Southern EU

**Northern EU**